VENTILATOR
bayoung

Specifications

AC Axial Fan

Model : YWF2E-250

Type : S-E5Z

Coding : E04020055

Version: V1.0

Date : 2022.03.02


Version	Status	Version update instructions	Date	DRN BY	CHK BY
V1.0	Effective	Initial release	2021-03-02	JX.Chen	XQ.Chen

VENTILATOR
bayoung

Standards

- GB12350 《*Safety Requirments of small Power motors*》
- EN60335-1 《*Safety Requirments of Household of Similar Electrical Appliances*》
- The level of balance is in accordance with ISO 1940, G4.0
- Vibration testing and velocity is performed according to JB/T8689.
- This product is certified by China CCC and EU CE
- ISO 9001 quality system certification
- Standard of noise test:ISO 13347 《*Determination of fan sound power levels under standardized laboratory conditions*》
- The fan performance data is accurate and reliable, conforming to GB/T1236-2017 and 《*Industrial fans-performance testing using standardize dairways*》 in ISO5801-2007 standards.

Product Drawings



VENTILATOR
bayoung

Technical Parameters

Power supply	Phase	1
Frequency	HZ	50
Wiring	-	-
Capacitance	μF	4.0
Input Voltage	V	220
Input Current	A	0.59
Input Power	W	135
Rated Speed	r/min	2435
Fan Noise	dB(A)	75
Fan Steering		Counterclockwise(From the motor)
Fan Life	h	40000
Fan Weight	kg	-
Protection Level		IP54
Insulation Class		F
Balance Level		G4.0
Ambient Temperature	℃	-40~+60
Environment Humidity		≤90%RH
Impeller Material		Metal
Spray Color		-
Operating Status		S1

VENTILATOR
bayoung

Label

VENTILATOR
bayoung


External Rotor Axial Fan

YWF2E-250 S-E5Z E04020055

220V 50Hz 0.59A 135W 4μF/450V

2435r/min 1565m³/h 120Pa CL.F Date:2022.XX


Product wiring diagram



VENTILATOR
bayoung

Product Performance

Airflow-static pressure curve:



St.P.	Air Flow	Speed	Votage	Freq.	Current	Power
Pa	m3/h	RPM	V	Hz	Amp	W
1	1465	2582	235	50	0.52	120
36	1302	2532	234	50	0.54	125
53	1201	2510	233	50	0.55	127
67	1099	2483	234	50	0.56	131
80	1000	2450	233	50	0.57	131
90	900	2440	234	50	0.58	135
98	799	2430	233	50	0.58	134
100	700	2441	233	50	0.57	133
118	600	2411	232	50	0.59	136
143	499	2333	232	50	0.62	143